



SILENCIADOR MW SPL




| | Código | A | B ± 0.2% | F | L ± 3% |
|-------------------------------------|-------------|-------|----------|------------|--------|
| Materiales: | W0970530062 | G 1/8 | 15.4 | 6.2 ± 0.5 | 27 |
| Resina acetálica negra insonorizada | W0970530063 | G 1/4 | 19.6 | 8 ± 0.5 | 35 |
| Fonoabsorbente | W0970530064 | G 3/8 | 24.7 | 11.3 ± 0.5 | 47 |
| | W0970530065 | G 1/2 | 24.7 | 10.7 ± 0.5 | 47 |
| | W0970530066 | G 3/4 | 48 | 18 ± 1 | 96 |
| Características | W0970530067 | G 1 | 48 | 18 ± 1 | 97 |
| Pmáx: 6 bar | | | | | |
| Temp.: -10°C ÷ +60°C | | | | | |

SILENCIADOR MW SPL-F




| | Código | A | B ± 0.2% | F ± 0.5 | L ± 3% | CH |
|------------------------|-------------|-------|----------|---------|--------|----|
| Materiales: | W0970530072 | G 1/8 | 16.3 | 5.5 | 29 | 10 |
| Resina acetálica negra | W0970530073 | G 1/4 | 20 | 7.4 | 36.5 | 13 |
| Filtro | W0970530074 | G 3/8 | 24.8 | 11 | 47 | 17 |
| | W0970530075 | G 1/2 | 24.8 | 11 | 47 | 17 |
| Características | | | | | | |
| Pmáx: 12 bar | | | | | | |
| Temp.: -10°C ÷ +60°C | | | | | | |

REGULADOR DE DESCARGA SILENCIADO MW SVE




| | Código | A | F | L ± 0.5 | CH |
|------------------------------|-------------|-------|------------|-------------|----|
| Materiales: | W0970520001 | G 1/8 | 6.7 ± 0.5 | 19 - 23 | 13 |
| Latón niquelado | W0970520002 | G 1/4 | 7.4 ± 0.5 | 21 - 24.5 | 15 |
| Bronce sinterizado niquelado | W0970520003 | G 3/8 | 9.7 ± 0.5 | 23.5 - 29.5 | 22 |
| Muelle de acero | W0970520004 | G 1/2 | 10.6 ± 0.5 | 23 - 28 | 22 |
| | W0970520005 | G 3/4 | 12 ± 1 | 29 - 35 | 30 |
| Características | W0970520006 | G 1 | 13.8 ± 1 | 27 - 34 | 36 |
| Pmáx: 12 bar | | | | | |
| Temp.: -10°C ÷ +80°C | | | | | |

REGULADOR DE DESCARGA SILENCIADO MW SVL




| | Código | A | F | L ± 0.5 | CH | CH1 |
|------------------------------|-------------|-------|------------|-------------|----|-----|
| Materiales | W0970520010 | M5 | 4 ± 0.5 | 17 ÷ 27 | 8 | 6 |
| Latón niquelado | W0970520009 | M7 | 4.5 ± 0.5 | 19 ÷ 31 | 8 | 5.5 |
| Bronce sinterizado niquelado | W0970520011 | G 1/8 | 7 ± 0.5 | 31 ÷ 40 | 16 | 9 |
| | W0970520012 | G 1/4 | 7.5 ± 0.5 | 30 ÷ 37.5 | 16 | 9 |
| | W0970520013 | G 3/8 | 10.5 ± 0.5 | 37.5 ÷ 51.5 | 22 | 9 |
| Características | W0970520014 | G 1/2 | 12.4 ± 0.5 | 39.5 ÷ 47.5 | 22 | 9 |
| Pmáx: 12 bar | W0970520015 | G 3/4 | 12.4 ± 1 | 56.5 ÷ 81 | 30 | 13 |
| Temp.: -10°C ÷ +80°C | W0970520016 | G 1 | 12.4 ± 1 | 58.5 ÷ 84.5 | 36 | 13 |

REGULADOR DE DESCARGA MW DSN



| | Código | A | B | CH | CH1 |
|----------------------|-------------|-------|-------|----|-----|
| Materiales: | W0970520021 | G 1/8 | G 1/8 | 12 | 12 |
| Latón niquelado | W0970520022 | G 1/4 | G 1/8 | 14 | 16 |
| | W0970520023 | G 3/8 | G 1/4 | 19 | 17 |
| | W0970520024 | G 1/2 | G 1/4 | 24 | 22 |
| Características | | | | | |
| Pmáx: 12 bar | | | | | |
| Temp.: -10°C ÷ +80°C | | | | | |

REGULADOR DE DESCARGA MW DSE



| | Código | A | F | L ± 0.5 | CH |
|----------------------|-------------|-------|-----------|-----------|----|
| Materiales: | W0970520031 | G 1/8 | 7.5 ± 0.5 | 16.8 - 20 | 14 |
| Latón niquelado | W0970520032 | G 1/4 | 10 ± 0.5 | 21.5 - 29 | 17 |
| Características | | | | | |
| Pmáx: 12 bar | | | | | |
| Temp.: -10°C ÷ +80°C | | | | | |